



MAKINEX®

Earth Moving 25hp Mini Stand-On Skid Steer



890mm Width



25 Horsepower



1 tonne Tipping Capacity

The Makinex 25hp Mini Stand-On Skid Steer delivers powerful performance in a compact design, making it ideal for tight job sites where manoeuvrability is key. With a width of just 890mm, this versatile machine easily fits through narrow spaces while offering an impressive tipping capacity of 1,010 kg. Powered by a Kubota D1105 diesel engine, it delivers 24.7hp with smooth hydraulic operation, ensuring efficiency and reliability for heavy-duty lifting, grading, and material handling. The Makinex Skid Steer features premium, globally sourced parts, including Sumitomo Riko hydraulic lines (Japan), Bondioli & Pavesi pumps (Italy), Walvis control valves, Danfoss motors, and Donaldson filtration.



IDEAL FOR:



**Tight-Space
Excavation**



**Material
Handling**



**Landscaping
& Site Prep**



**Demolition & Debris
Removal**



**Utility & Trenching
Work**



**Agriculture &
Farming**

SPECIFICATIONS:

DIMENSIONS (STD)		PERFORMANCE	
Height to Bucket Hinge Pin, max	1.93 m	Ground drive speed, forward and reverse	6.3 km/h
Operating Height, max std.bucket	2.7 m	Ground pressure, 8 in (200 mm) tracks	0.35 bar
Height	1.3 m	Angle of Departure	22°
Length without Attachment	1.8 m	Tipping capacity	1010 kg
Length with Standard Bucket	2.5 m	Operating capacity (35% of tipping capacity)	354 kg
Ground Clearance	145 mm	Machine weight (no attachment, fluids full)	1230 kg
Ground Contact Length	960 mm	Auxiliary Hydraulic Flow	48 L/min
Width	890 mm	Auxiliary Hydraulic Pressure	180 Bar
POWER		Battery 12 V; 60 Ah	475 cold cranking amps @ -18°C
Engine Kubota D1105 diesel	EU Stage V/ EPA Tier 4 Final		
Number of cylinders	3	FLUID CAPACITIES	
Displacement	1.123 L	Fuel tank	34 L
Bore	78 mm	Engine oil, with filter	5 L
Stroke	78.4 mm	Hydraulic System	45 L
Gross power rating (per SAE J1955)	18.2 kW		
Rated engine speed	3000 rpm		




FEATURES:



1. Stand-On Operator Platform



2. Compact 890mm Width



3. Kubota D1105 Diesel Engine



4. 1 Tonne Tipping Capacity



5. 48 L/min Hydraulic Flow




6. 6.3 km/h Travel Speed



7. Two sets of Quick Couplers



8. Wide selection of Attachments



9. Heavy Duty Frame



10. Easy access to all Engine Components

MAKINEX MINI DUMPER RANGE



1. Cormidi C40



2. Cormidi C60



3. Cormidi C85